

Turbo Mower

The Turbo Mower Elite, Euro, Open and Pro range offers operators a huge choice of cutting widths at very cost effective prices.

A well designed and constructed range, the Turbo Mower is built with durability and ease-of-use in mind – a low maintenance machine that is simple to operate.

Key Features

- Choice of cutting widths available
- Front mount options
- 1.3 and 1.5 manual offset
- Hydraulic offset standard on 1.9m and above
- Standard fitted roller and side skids
- Cat II three point linkage mounted
- Over run slip clutch protected



Want to know more about the Turbo Mower range?

Scan the QR code to the left with a smart phone or tablet and compatible app to instantly view the page.

Alternatively visit: www.bomford-turner.com/landscape/flail-mowers-and-toppers/turbo-mower/



Product Specification

● Standard ○ Optional — Not Available

Turbo Mower	ELITE 130	ELITE 150	ELITE 190	ELITE 225	ELITE 245	ELITE 270
Working Width	1.3m / 4'3"	1.45m / 4'9"	1.9m / 6'4"	2.26m / 7'5"	2.42m / 8'	2.72m / 8'10"
Overall Width	1.47m / 4'10"	1.63m / 5'4"	2.1m / 6'10"	2.45m / 8'	2.6m / 8'6"	2.9m / 9'6"
Weight	213kg / 469lbs	237kg / 522lbs	451kg / 994lbs	554kg / 1221lbs	596kg / 1313lbs	632kg / 1393lbs
Hydraulic Offset	—	—	Hyd Operated	Hyd Operated	Hyd Operated	Hyd Operated
Fully offset left of centre	—	—	400mm / 15½"	400mm / 15½"	400mm / 15½"	400mm / 15½"
PTO speed	540	540	540	540	540	1000
Front mount	—	—	—	—	—	—
No. of Flails (Whale Tail)	18	20	24	28	30	34
Power requirements	30-37hp	35-40hp	45-60hp	55-75hp	65-90hp	75-100hp
Cutting height	32-111mm 1¼"-4½"	32-111mm 1¼"-4½"	32-111mm 1¼"-4½"	32-111mm 1¼"-4½"	32-111mm 1¼"-4½"	32-111mm 1¼"-4½"
Roller size	114mm / 4½"	114mm / 4½"	140mm / 5½"	140mm / 5½"	140mm / 5½"	140mm / 5½"

Turbo Mower	EURO 250	EURO 280	OPEN 250	OPEN 280	PRO 250	PRO 270	PRO 300
Working Width	2.5m / 8'3"	2.8m / 9'2"	2.44m / 8'	2.77m / 9'1"	2.45m / 8'	2.70m / 8'10"	3.00m / 9'10"
Overall Width	2.67m / 8'9"	3m / 9'10"	2.67m / 8'9"	3m / 9'10"	2.73m / 8'11"	2.98m / 9'9"	3.28m / 10'9"
Weight	867kg / 1911lbs	939kg / 2070lbs	859kg / 1893lbs	928kg / 2045lbs	1210kg / 2667lbs	1284kg / 2830lbs	1390kg / 3064lbs
Hydraulic Offset	Hyd Operated	Hyd Operated	Hyd Operated	Hyd Operated	Hyd Operated	Hyd Operated	Hyd Operated
Fully offset left of centre	500mm / 19¾"	500mm / 19¾"	500mm / 19¾"	500mm / 19¾"	400mm / 15¾"	400mm / 15¾"	400mm / 15¾"
PTO speed	1000	1000	1000	1000	1000	1000	1000
Front mount	●	●	—	—	●	●	●
No. of Flails (Whale Tail)	28	32	28	32	20	24	26
Power requirements	65-110hp	75-110hp	65-100hp	75-110hp	68-80hp	80-120hp	95-135hp
Cutting height	43-88mm 1¾"-3½"	43-88mm 1¾"-3½"	32-111mm 1¼"-4½"	32-111mm 1¼"-4½"	45-157mm 1¾"-6¼"	45-157mm 1¾"-6¼"	45-157mm 1¾"-6¼"
Roller size	170mm / 6¾"	170mm / 6¾"	170mm / 6¾"	170mm / 6¾"	220 / 8¾"	220 / 8¾"	220 / 8¾"

Wear skirts

Simple greasing and replaceable skirts.

Float function

Slotted holes for simple float function.

Easy adjustment

Simple belt tensioning system with oil filled drive tube.



Twin Headstock Options

Heavy duty rollers and bearing assemblies with scraper bars.

Twin headstock options available on selected models.