

**The best end result begins  
with the Herder mowing bucket**



**MOWING BUCKET MR**



# Achieve more with the Herder mowing bucket

Everyone wants a good mowing result, but everyone also wants an outline of the costs. With its fifth generation 'MR' mowing buckets, Herder proves you that you can achieve both. Herder mowing buckets have been developed to perform to the full in all conditions.

This starts with the well thought-out design of the mowing bucket and all of the moving parts. Moreover, exclusive use is made of high-quality materials which guarantee a long lifespan. A unique design, the application of the best materials in combination with quality workmanship gives an unequalled tool. A mowing bucket that performs everywhere and at all times. The MRL Mowing Bucket, a lighter mowing bucket model, is ideal for the Herder Grenadier and medium-sized excavators. The Mowing Bucket MRZ, the heavier version of the mowing bucket, is suitable for wheel and crawler excavators. You can also choose from different widths, from 2.5 to 5.5 metres. You can even reach widths of up to 8.6 metres by combining two mowing buckets. Furthermore Herder has two 'ultra-light' models in its range, with 2 and 2.5 metres working widths. These are ideal for a mini excavator in connection with the weight/stability. You simply achieve more with the Herder mowing bucket.



*A Herder mowing bucket on a Herder Grenadier: 2 premium products from the Herder range.*



*The Herder mowing bucket can be attached directly to the excavator.*



*An excavator with the mowing bucket on an extension piece for extra reach.*



## Details - mowing bucket - standard model



*Low-maintenance knife head connection with standard long knife attachment.*



*Cutter bar with spring pressure holder for continuous knife pressure.*



*The mowing bucket driving gear is fixed by means of 12 bolts.*

*Comes as standard with low-maintenance self-sharpening T knives.*



## Mowing bucket options



*The volume of the mowing bucket can be increased with extension and side racks.*



*The mowing bucket can have a Herder connection or an excavator connection as required.*



*G knives that you can sharpen yourself are available as an option. Herder can supply special grinders for them if desired.*



*A mowing bucket with a working width of 8.60 metres helps you achieve more in less time.*



*With the tilt cylinder you can keep the transport position inside 3 metres (maximum allowable width) for the 4.3 and 5.5 metre mowing buckets.*



# TECHNICAL SPECIFICATIONS

Application	Type/width in cm	Frame height in cm	Oil consumption in L/min.	Weight in kg
<b>Mini excavators</b>	MSFT200.B	40	approx. 22	approx. 190
	MSFT250.B	40	approx. 22	approx. 215
<b>Tractors/</b>	MRLT 250.B	52	approx. 40	approx. 303
<b>Medium excavators &lt; 8 tonnes</b>	MRLT 300.B	52	approx. 40	approx. 328
	MRLT 430.B	52	approx. 40	approx. 403
	MRLT 550.B	52	approx. 40	approx. 483
<b>Excavators &gt; 8 tonnes</b>	MRZT 250.B	52	approx. 40	approx. 331
	MRZT 300.B	52	approx. 40	approx. 360
	MRZT 430.B	52	approx. 40	approx. 447
	MRZT 550.B	52	approx. 40	approx. 538

Maximum allowable oil pressure: 170 bar.



**You will achieve more with Herder**



MAIK-EN-04

[www.herder.nl](http://www.herder.nl)