



STANDARD & HEAVY DUTY

TrailKat

Mowers



TFR-HD 180



TK-120

DURABILITY INNOVATION

COMMITMENT



Pivot Hitch



Safety Cover



Cast Pan
Blade Carrier



WetCut available
as option on all
models



Offset Hitch

Specifications

| | TK-120 | TK-180 | TFR-HD120C | TFR-HD180C |
|----------------------------|--------------------|--------------------|--------------------|--------------------|
| Cutting Width | 126" | 180" | 126" | 180" |
| Overall Width | 133" | 187" | 139" | 190" |
| Overall Length | 183" | 183" | 192" | 192" |
| Transport Width, min | 88" | 96" | 88" | 88" |
| Deck Thickness | 7GA (3/16") | 7GA (3/16") | 7GA (3/16") | 7GA (3/16") |
| Weight (approx.) | 4,800 lbs. | 5,455 lbs. | 5,100 lbs. | 5,800 lbs. |
| Minimum PTO HP | 60 HP | 60 HP | 50 HP | 65 HP |
| Recommended PTO HP | 75 HP | 85 HP | 75 HP | 90 HP |
| Cutting Height | 2" to 14" | 2" to 14" | 1.5 to 17.5" | 1.5 to 17.5" |
| Ground Clearance | 13.5" | 13.5" | 17.5" | 17.5" |
| Cutting Capacity | 4.5" Material | 4.5" Material | 4" Material | 4" Material |
| Blade Overlap | 6.0" | 6.0" | 6.5" | 6.5" |
| Divider Gear Box Rating | 250 HP | 250 HP | 260 HP | 260 HP |
| Center/Wing Gearbox Rating | 225 HP | 225 HP | 210 HP | 210 HP |
| Blade Tip Speed | 540 PTO RPM | 540 PTO RPM | 540 PTO RPM | 540 PTO RPM |
| Center | 16,286 ft/min | 16,286 ft/min | 15,981 ft/min | 15,981 ft/min |
| Wing | 16,422 ft/min | 16,422 ft/min | 15,493 ft/min | 15,493 ft/min |
| Wing Working Range | 25° down to 90° up | 25° down to 90° up | 25° down to 90° up | 25° down to 90° up |
| Walking Axle Center | Optional | Optional | Standard | Standard |
| Walking Axles Wings | Available option | Available option | Available option | Available option |
| LED Light Kit | Standard | Standard | Standard | Standard |
| Required Tractor Remotes | 2 Remotes | 3 Remotes | 2 Remotes | 3 Remotes |

Specifications

Tiger's Offset Hitch (TOH)

Allows the tractor to remain on the road while the mower is fully in the ditch.
Provides operator safety and comfort with the ability to mow steep ditches without leaving the road.
Attaches to 10" and 15" Trailkat mowers.

Tiger's Offset Hitch can be used with 540 or 1000 PTO

Swivel mounted gear boxes designed to keep drive shafts in line at all times.

Patented strut arm allows backing up like 2 wheel trailer.

Low center of gravity design provides visibility to cutter head.

Transport width is 102"

Machine weight 2,757 lbs.

Offset Hitch extends mower to the right rear of tractor.

Drive line rated at 136 hp.

Gear boxes rated at 200 hp continuous.

LED lights included.

Tiger Trailkat



The Tiger Trailkat pull behind mowers in 5', 6' and 7' sizes are designed to add flexibility, productivity and value to your tractor.

Built strong to handle your toughest mowing terrain with ease.

Fast and easy hook up with Tiger's 3 point hitch design, this mower can make quick work of your mowing and can disconnect when finished so tractor can be used for other work.

SPECIFICATIONS

| | TK-5 | TK-6 | TK-7 |
|------------------------|-----------------|-----------------|------------------------------|
| Cutting Width | 60" | 72" | 84" |
| Overall Width | 66" | 78" | 88.5" |
| Overall Length | 88" | 100" | 130" |
| Deck Thickness | 10Ga | 10 Ga | 10Ga |
| Weight (approx.) | 988 lbs. | 1,158 lbs. | 1,350lbs. |
| Hitch | CAT I & QH | CAT I & QH | CAT I & QH |
| Gearbox Rating | 130 HP | 130 HP | 130 HP |
| Recommended PTO HP | 35 HP | 45 HP | 60 HP (Lift) 45 HP (Pull) |
| Cutting Height (Min) | 1 1/2" | 1 1/2" | 1 1/2" |
| Cutting Capacity (Max) | 2" | 2" | 2" |
| Side Skirt | 10 Ga. x 9 1/4" | 10 Ga. x 9 1/4" | 10 Ga. x 9 1/4" |
| Slip Clutch | Standard | Standard | Standard |
| Blade Tip Speed | 13,572 ft/min | 16,286 ft/min | 16,328 ft/min |



Dealer Info:



Tiger Corporation
 3301 N. Louise Ave
 Sioux Falls, SD 57107
 800-843-6849
 www.tigermowers.com
 An Alamo Group Company



MADE WITH PRIDE IN THE USA

Specifications are subject to change without notice. Optional equipment may be shown. One Year Warranty on all products.